

塑料螺母座紧固件



塑料螺母座紧固件的优点

- ◆ 夹紧力最大化
- ◆ 与DELTA PT® 螺丝配合安装，产品安全性得到极大提高
- ◆ 容易装配
- ◆ 无需表面处理，抗腐蚀力强
- ◆ 可回收
- ◆ 如果散装包装，货物不会互锁
- ◆ 不同的颜色保证过程控制安全
- ◆ 可以采用不同材料
- ◆ 比金属件轻便
- ◆ 可以多次重复拆装

Benefits of the EJOT EASYboss®

- ◆ *Maximization clamp force*
- ◆ *Safe assembly with DELTA PT® screw*
- ◆ *No risk of injury*
- ◆ *Without surface treatment , corrosion and media resistance*
- ◆ *Recyclable*
- ◆ *The parts will not interlocking if bulk package*
- ◆ *Different colour ensure process control safety*
- ◆ *Can adopt different raw material*
- ◆ *Weight advantage over metal parts*
- ◆ *Multiple repeat assemblies*



EJOT EASYboss® V是一种创新的紧固件，它能用于组装可变厚的零件。弹性的设计可以预装在不同厚度的板材上，并产生一定的夹紧力。

EJOT EASYboss® V is a novel fastening element that can be used for assembly on varying thickness of components. The spring supported boss allows pre-assembly on varying snap-on wall thickness of the substructure. At the same time the retention force for captive pre-assembly is applied.

特点：

卡在零件边缘进行安装
可应用于不同厚度的板材
易于组装/拆卸

材料：PA

与DELTA PT® 螺丝配合使用

Characteristics:


Assembly by means of a snap fit to the edge

Variable snap-on thickness

Easy assembly disassembly

Material: PA

Optimized for DELTA PT® screws



EJOT EASYboss® 是金属卡扣的替代品。

EJOT EASYboss® was developed as an alternative to sheet metal clips.

特点：

卡在零件边缘进行安装
负载能力高
易于拆卸

材料：POM, PA(GF), PBT, PP-GF30

与之配合的DELTA PT® 螺丝，直径为3.5-6mm

板材厚度：1.0-6.0mm

旋入长度：5.0-15.0mm

Characteristics:

Assembly by means of a snap fit to the edge

High load capacity of the fastening spot due to big bearing surface


Easy disassembly

Materials: POM, PA(GF), PBT, PP-GF30

Optimized for DELTA PT® screw with diameter of 3.5-6mm

Thickness of substructure: 1.0-6.0mm

Insertion depth: 5.0-15.0mm




应用案例 Applications Example



汽车车灯
Auto headlamp
assembly



汽车中控系统
Auto central control
system assembly



换档器底座
Gear shift pedestal
assembly



摩托车左右护板
Motorbike left and right
cover sheet assembly